

Safety Data Sheet

SUMNER LABS 210 - LOW VOC

Section 1. Identification

Product Identifier	SUMNER LABS 210 - LOW VOC		
Synonyms	N/A		
Manufacturer Stock Numbers	23306		
Recommended use	Cleans and polishes boats, cars, airplanes, motorcycles, acrylic windows, skylights, picture frames and many more!		
Uses advised against	N/A		
Manufacturer Contact			
Address	Shield Packaging Co., Inc. 50 Oxford Ave. Dudley, MA, 01571 USA		
	Phone	Emergency Phone	Fax
	(508) 949-0900	(800) 424-9300 CHEMTREC CHEMTREC 24 HR. Emergency Telephone Number	(508) 943-1473

Section 2. Hazards Identification

Classification	ASPIRATION HAZARD - Category 2 EYE DAMAGE/IRRITATION - Category 2B FLAMMABLE AEROSOLS - Category 1 GASES UNDER PRESSURE - Compressed gas HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD - Category 3 SKIN CORROSION/IRRITATION - Category 3 SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3
Signal Word	Danger

Pictogram



Hazard Statements

May cause drowsiness or dizziness
Causes eye irritation
Causes mild skin irritation
Contains gas under pressure; may explode if heated
Extremely flammable aerosol
Harmful to aquatic life with long lasting effects
May be harmful or fatal if swallowed and enters airways

Precautionary Statements

Response

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If swallowed: Immediately call a poison center for medical advice. DO NOT induce vomiting.

Prevention

Avoid breathing dust/fume/gas/mist/ vapors/spray.
Avoid release to the environment
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.

Storage

Store in a cool, dry, well-ventilated area away from heat and ignition sources.

Disposal

Dispose of contents/container in accordance with all local, state, national and international regulations.

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

No Data Available

Section 3. Ingredients

CAS	Ingredient Name	Weight %
64742-47-8	HYDROTREATED PETROLEUM DISTILLATES*	25-35 %
106-97-8	BUTANE*	1.4% - 7.21%
74-98-6	PROPANE*	0.47% - 7.11%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Skin Contact:

Wash off with mild soap and water. If irritation develops or persists consult physician.

Eye Contact: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing the eye. If irritation persists, seek medical advice.

Inhalation: Remove affected person to fresh air.

Ingestion: If swallowed, IMMEDIATELY call a poison control center or doctor for treatment advice. Do not induce vomiting.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/OSHA (approved or equivalent) and full protective gear. Self-contained respiratory protection should be provided for firemen fighting in buildings or confined areas. Keep cans cool to prevent possible bursting. Carbon Dioxide, dry chemical or foam. Do not use water jet as it will spread the fire.

Unsuitable Extinguishing Media N/A

Section 6. Accidental Release Measures

Spill Cleanup Wipe or mop up spill immediately.

Personal Precautions: Wear appropriate personal protection equipment. For personal protection see section 8.

Section 7. Handling and Storage

Storage: Store in a cool, dry well ventilated area away from heat and ignition sources. KEEP OUT OF THE REACH OF CHILDREN

Handling Avoid high temperatures that may elevate component pressure above container rating. Cylinders should be stored upright with valve protection cap in place.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	HYDROTREATED PETROLEUM DISTILLATES*	200mg/m ³	200mg/m ³	200mg/m ³
	BUTANE*	N/A	N/A	N/A
	PROPANE*	NEppm	1000ppm	N/A

Personal Protective Equipment N/A

Protective Measures: Room ventilation is generally adequate with expected normal use. Use local exhaust as necessary to keep vapor concentration low.

Eyes and Face Protection: Not required when used as directed.

Section 9. Physical and Chemical Properties

Physical State	Aerosol
Color	White, Milky opaque
Odor	Slight solvent odor
Odor Threshold	N/A
Solubility	Insoluble in water
Partition coefficient Water/n-octanol	N/A
VOC%	< 8%
Viscosity	N/A
Specific Gravity	0.92
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	-116F
FP Method	Closed Cup
pH	N/A
Melting Point	N/A
Boiling Point	N/A
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	> 1
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	N/A
Vapor Density	> 1

Section 10. Stability and Reactivity

Stability: This is a stable material.
Possibility of Hazardous Reactions: Will not occur.
Conditions to Avoid: Excessive storage temperatures and contact with extremely hot surfaces

Section 11. Toxicological Information

Serious Eye Damage/Eye Irritation: Eye Damage/Irritation Category 2B
Skin Corrosion/Irritation: Skin Corrosion/Irritation Category 2
Inhalation: Specific target organ toxicity (single exposure): STOT Single Exposure 3

Ingestion

Harmful or fatal if swallowed and aspirated into lungs

Section 12. Ecological Information

Ecotoxicity: This product may be toxic to fish or other aquatic organisms. Do NOT discharge effluent containing this product into sewer systems.

Section 13. Disposal

Disposal Method: All wastes must be handled and disposed of in accordance with local, state, national and international regulations.

Section 14. Transport Information

UN Number 1950
UN Proper Shipping Name AEROSOL, FLAMMABLE
DOT Classification 2.1
Packing Group N/A
Additional Information IATA - UN Number: 1950
IATA - Proper Shipping Name: Aerosol, Flammable
IATA - Transport Hazard Class: 2.1
IATA - Packing Group N/A

IMDG - UN Number: 1950
IMDG - Proper Shipping Name: Aerosol, Flammable
IMDG - Transport Hazard Class: 2.1
IMDG - Packing Group" N/A

Section 15. Regulatory Information

TSCA INVENTORY All components of this product are either on the Toxic Substances Control Act (TSCA) Inventory List or exempt.

Section 302 Extremely Hazardous Substances (40 CFR 355, Appendix A): There are no SARA Title III Section 302 Extremely Hazardous Substances present in this product (40 CFR 355, Appendix A).

Section 313 Toxic Release Inventory (40 CFR 372): This product contains no toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and 49 CFR 372.

Section 311/312 (40 CFR 370): (X) Acute (Immediate)

(X) Sudden pressure release hazard (X) Fire

GRAS List: The components of the propellants (propane, and normal butane) are listed on the Generally Recognized As Safe (GRAS) List, Part 184, Sub-Part B, Sec. 184.1165 and 184.1655 (Code of Federal Regulations).

Section 16. Other Information

Revision Date

4/15/2019

CAS

This product is a MIXTURE. NO CAS exists for it.

Environmental
Precautions:

Avoid dispersal of spilled material and runoff, also avoid contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Contaminated absorbent and wash water should be disposed of according to local, state and federal regulations.

Additional Information

The information contained in this Safety Data Sheet is furnished without warranty of any kind, expressed or implied. Information in this Data Sheet has been assembled by the manufacturer based on its own studies and on the work of others and is believed to be correct as of the date issued. However, no warranty of any kind is expressed or implied as to the accuracy, completeness, or adequacy of the information obtained herein.